


Series **ST**

Polyurethane Tubing

● FOR GENERAL AIR PRESSURE TUBING



How to Order

ST0425

BU

1

2

1 Indication of Tube Type

2 Color Indication

- B : Black
- BU : Blue
- Y : Yellow
- C : Clear

Series Table

◎-100m

	Metric-size(series ST)							
Description	ST0402	ST0425	ST0604	ST0805	ST0855	ST1065	ST1208	ST1209
Tube O.D.mm	4	4	6	8	8	10	12	12
Tube I.D.mm	2	2.5	4	5	5.5	6.5	8	9
Weight(kg)	1.1	2.0	2.2	4.0	3.6	6.0	8.0	7.8
Black(B)	◎	◎	◎	◎	◎	◎	◎	◎
Blue(BU)	◎	◎	◎	◎	◎	◎	◎	◎
Yellow(Y)	◎	◎	◎	◎	◎	◎	◎	◎
Clear(C)	◎	◎	◎	◎	◎	◎	◎	◎

Specifications

Max. Operating Pressure	100 PSI (7kgf/cm ²)				
Burst Pressure	Refer to burst pressure characteristics curve.				
Note 1) Minimum Bending Radius Inch(mm)	0.39(10)	0.59(15)	0.79(20)	1.07(27)	1.38(35)
Operating Temperature	-20~60 °C(-4~140° F)				
Material	Polyurethane				

Note 1) The value for bending radius is at a temperature of -21°C(-4°F)
 (Reference) The inch sizes φ5/32" and φ5/16" are equivalent to φ4 and φ8 mm